Journal of Testing and Evaluation
Author Index
Volume 26, 1998

Number	Month of Issue	Pages
1	January	1–82
2	March	83–176
3	May	176–300
4	July	301–304
5	September	405–526
6	November	527–642

A

Al-Smadi, ZA: *see* Obaidat, MT and Al-Smadi, ZA

Ali, AH: *see* Goulias, DG and Ali, AH

Allam, MM: *see* Robinson, RG and Allam, MM

Anantharaman, S: *see* Sriharsha, HK, Anantharaman, S, Chatterjee, S, and Pandey, RK

Anderson, SA: *see* Zhu, JH and Anderson, SA

Arsene, S and Bai, J: New approach to measuring transverse properties of structural tubing by a ring test—experimental investigation, Jan., 26

B

Bai, J: *see* Arsene, S and Bai, J

Barbato, G: *see* Bray, A, Barbato, G, Franceschini, F, Levi, R, Romano, D, and Zompi, A

Batchelor, AW: *see* Fu, Y, Gu, Y, and Batchelor, AW

Bledzki, AK and Gassan, J: Dissipated energy of composite materials—Part I: Cyclic dynamic stress, Sept., 467

Bonenberger, RJ, Dally, JW, and Fourney, WL: Procedure for fracture toughness testing using a chevron-notched crack-arrest specimen, July, 376

Bovsunovsky, AP and Kratko, AG: Shape of mechanical hysteresis loops for metals under harmonic loading, Jan., 31

Braam, JJ and van der Zwaag, S: Statistical evaluation of the staircase and the ArcSin $\sqrt{P}$ methods for determining the fatigue limit, March, 125

Bradtmueller, JP, Hunt, MO, and Shook, SM: Mechanical properties of laminated veneer lumber via five-point bending test, March, 132

Bray, A, Barbato, G, Franceschini, F, Levi, R, Romano, D, and Zompi, A: Automatic procedure for evaluation of Young's Modulus of metallic materials, Jan., 64

Bremner, T: *see* Rogers, AD, Lee-Sullivan, P, and Bremner, T

Brown, K: *see* Landes, JD and Brown, K

Burch, IA, Ritter, JC, Saunders, DS, and Underwood, JH: Crack arrest fracture toughness testing of naval construction steels, May, 269

Butt, DP: *see* Zhu, YT, Butt, DP, Taylor, ST, and Lowe, TC

C

Carey, RF: *see* Lytle, CD, Clavet, CR, Chaput, MP, Varney, GW, To, TM, and Carey, RF

Chaput, MP: *see* Lytle, CD, Clavet, CR, Chaput, MP, Varney, GW, To, TM, and Carey, RF

Chatterjee, S: *see* Sriharsha, HK, Anantharaman, S, Chatterjee, S, and Pandey, RK

Chen, G: *see* He, Q, Chen, G, and Zhang, S

Cheng, YW, Filla, BJ, and Tobler, RL: Design and performance of an automated test facility for hot-compression testing, Jan., 38

Chiang, FP: *see* Du, ML, Chiang, FP, Kagwade, SV, and Clayton, CR

Chinnadurai, R: *see* Verma, BB, Pandey, RK, and Chinnadurai, R

Chui, YH and Ni, C: Stress-strain relationship of common wire nails under reversed cyclic loading, Sept., 420

Church, JR and Tew, BW: Bearing strength of white oak pegs in red oak and douglas fir timbers, March, 109

Clavet, CR: *see* Lytle, CD, Clavet, CR, Chaput, MP, Varney, GW, To, TM, and Carey, RF

Clayton, CR: *see* Du, ML, Chiang, FP, Kagwade, SV, and Clayton, CR

Coyne, L: *see* Pierdominici, VJB, Jr., Doucette, JM, Coyne, L, Cyr, WH, Thomas, DP, and Lytle, CD

Cramer, SM: *see* Saliklis, EP, Cramer, SM, and Hermanson, JC

Cyr, WH: *see* Pierdominici, VJB, Jr., Doucette, JM. Coyne, L, Cyr, WH, Thomas, DP, and Lytle, CD

D

Dally, JW: *see* Bonenberger, RJ, Dally, JW, and Fourney, WL

Donovan, A: *see* Scott, W and Donovan, A

Doucette, JM: *see* Pierdominici, VJB, Jr., Doucette, JM, Coyne, L, Cyr, WH, Thomas, DP, and Lytle, CD

Du, ML, Chiang, FP, Kagwade, SV, and Clayton, CR: Influence of corrosion on the fatigue properties of Al 7075-T6, May, 260

DuQuesnay, DL: *see* Gong, Z, DuQuesnay, DL, and McBride, SL

E

Eadie, RL: *see* Lin, G, Skrzypek, S, Li, D, and Eadie, RL

Echelberger, WF, Jr.: *see* Gunaratne, M, Stinnette, P, Mullins, AG, Kuo, CL, and Echelberger, WF, Jr.

Elias, V: *see* Salman, A, Goulias, D, and Elias, V

© 1998 by the American Society for Testing and Materials

F

Fatemi, A: *see* Yang, L and Fatemi, A

Ferron, G: *see* Mussot-Hoinard, G and Ferron, G

Filla, BJ: *see* Cheng, YW, Filla, BJ, and Tobler, RL

Finch, RD: *see* Wang, Z, Man, XTC, Finch, RD, and Jansen, BH

Foo, KY and Kandhal, PS: Adapting superpave technology to design of hot recycled mixes, May, 203

Fourney, WL: *see* Bonenberger, RJ, Dally, JW, and Fourney, WL

Franceschini, F: *see* Bray, A, Barbato, G, Franceschini, F, Levi, R, Romano, D, and Zompi, A

Friedersdorf, FJ and Holcomb, GR: Pin-on-disk corosion-wear test, July, 352

Fu, Y, Gu, Y, and Batchelor, AW: Evaluation of the fracture toughness of the deep-carburized layer, May, 198

G

Garnaes, J: *see* Jensen, CP, Jorgensen, JF, Garnaes, J, Picotto, GB, and Gori, G

Gassan, J: *see* Bledzki, AK and Gassan, J

Gillenwater, MW, Hartwig, KT, and Hua, CY: Eddy current decay and resistivity measurements on longitudinally grooved high-purity aluminum bars, July, 320

Giovanola, JH, Klopp, RW, and Kirkpatrick, SW: Note on one-point-bend impact fracture experiments with curved specimens, Jan., 79

Gomes, PTV: *see* Palma, ES, Lourenco, OR, and Gomes, PTV

Gong, Y and Norton, MP: Materials fatigue life distribution: a maximum entropy approach, Jan., 53

Gong, Z, DuQuesnay, DL, and McBride, SL: Measurement and interpretation of fatigue crack growth in 7075 aluminum alloy using acoustic emission monitoring, Nov., 567

Goree, JG: *see* Salivar, GC and Goree, JG

Gori, G: *see* Jensen, CP, Jorgensen, JF, Garnaes, J, Picotto, GB, and Gori, G

Gorzynski, M: *see* Singh, SP and Gorzynski, M

Goulias, D
Ali, AH: asphalt-rubber mixture behavior and design (wet process), July, 306
see Salman, A, Goulias, D, and Elias, V

Grosso, M: *see* Toropov, AI and Grosso, M

Gu, Y: *see* Fu, Y, Gu, Y, and Batchelor, AW

Guice, LK: *see* Straughan, WT, Tantirungrojchai, N, Guice, LK, and Lin, H

Gunaratne, M, Stinnette, P, Mullins, AG, Kuo, CL, and Echelberger, WF, Jr.: Compressibility relations for peat and organic soil, Jan., 1

H

Hamm, RW and Johnson, WS: International survey of small-crack research, March, 168

Hartwig, KT: *see* Gillenwater, MW, Hartwig, KT, and Hua, CY

He, Q, Chen, G, and Zhang, S: Measurement of fatigue-creep dynamic back stress and strain rate equation of a Fe-Ni-Cr alloy, Nov., 617

Hermanson, JC: *see* Saliklis, EP, Cramer, SM, and Hermanson, JC

Holcomb, GR: *see* Friedersdorf, FJ and Holcomb, GR

Hua, CY: *see* Gillenwater, MW, Hartwig, KT, and Hua, CY

Hunt, MO: *see* Bradtmueller, JP, Hunt, MO, and Shook, SM

I

Iskander, SK, Milella, PP, Pini, A, and Manneschmidt, ET: Crack-arrest testing of irradiated nuclear reactor pressure vessel steels at the Oak Ridge National Laboratory, Nov., 546

J

Jansen, BH: *see* Wang, Z, Man, XTC, Finch, RD, and Jansen, BH

Jensen, CP, Jorgensen, JF, Garnaes, J, Picotto, GB, and Gori, G: Vickers hardness indentations measured with atomic force microscopy, Nov., 532

Johnson, RL: *see* Schaeffer, SL, Johnson, RL, and Lewis, WB

Johnson, WS: *see* Hamm, RW and Johnson, WS

Jorgensen, JF: *see* Jensen, CP, Jorgensen, JF, Garnaes, J, Picotto, GB. amd Gori, G

Joyce, JA: Experimental justification for proposed changes to the measurement of K_{Ic} using ASTM E 399, Sept., 455

K

Kagwade, SV: *see* Du, ML, Chiang, FP, Kagwade, SV, and Clayton, CR

Kajiwara, G: X-ray piping diagnostic system, July, 346

Kandhal, PS: *see* Foo, KY and Kandhal, PS

Khoddam, S, Lam, YC, and Thomson, PF: Method of finding the effective length of the specimen used in the hot torsion test and recommendations on geometry of the test specimen, March, 157

Kim, K: Design and development of a high-speed bearing test apparatus, July, 301

Kirkpatrick, SW: *see* Giovanola, JH, Klopp, RW, and Kirkpatrick, SW

Klopp, RW: *see* Giovanola, JH, Klopp, RW, and Kirkpatrick, SW

Koan, KJ: *see* Mo, YL and Koan, KJ

Kratko, AG: *see* Bovsunovsky, AP and Kratko, AG

Kumaran, MK:
Alternative procedure for the analysis of data from the cup method measurements for determination of water vapor transmission properties, Nov., 575
Interlaboratory comparison of the ASTM standard test methods for water vapor transmission of materials (E 96–95), March, 83

Kuo, CL: *see* Gunaratne, M, Stinnette, P, Mullins, AG, Kuo, CL, and Echelberger, WF, Jr.

L

Laguros, JG: *see* Tian, P, Zaman, MM, and Laguros, JG

Lam, YC: *see* Khoddam, S, Lam, YC, and Thomson, PF

Landes, JD and Brown, K: Results from a round robin on a standard method for measurement of fracture toughness, July, 396

Landy, RA: *see* Segall, AE, Shelleman, DL, Pan, MJ, Landy, RA, and Nelson, BR

Lee-Sullivan, P: *see* Rogers, AD, Lee-Sullivan, P, and Bremner, T

Lee, Y-L, Wehner, TJ, Lu, M-W, Morrissett, TW, and Pakalnins, E: Ultimate strength of resistance spot welds subjected to combined tension and shear, May, 213

Levi, R: *see* Bray, A, Barbato, G, Franceschini, F, Levi, R, Romano, D, and Zompi, A

Lewis, WB: *see* Schaeffer, SL, Johnson, RL, and Lewis, WB

Li, D: *see* Lin, G, Skrzypek, S, Li, D, and Eadie, RL

Li, M, Xu, B-H, and Wu, Y-S: H_2-optimal control of random loading for a laboratory fatigue test, Nov., 619

Lin, G, Skrzypek, S, Li, D, and Eadie, RL: Monitoring crack advance using acoustic emission and combined acoustic emission and potential drop in Zr-2.5%Nb, Jan., 15

Lin, H: *see* Straughan, WT, Tantirungrojchai, N, Guice, LK, and Lin, H

Lourenco, OR: *see* Palma, ES, Lourenco, OR, and Gomes, PdTV

Lowe, TC: *see* Zhu, YT, Butt, DP, Taylor, ST, and Lowe, TC

Lu, M-W: *see* Lee, Y-L, Wehner, TJ, Lu, M-W, Morrissett, TW, and Pakalnins, E

Lytle, CD
Clavet, CR, Chaput, MP, Varney, GW, To, TM, and Carey, RF: Evaluation of three methodologies for testing disposable ENT endoscope sheaths as viral barriers, Nov., 587
see Pierdominici, VJB, Jr., Doucette, JM, Coyne, L, Cyr, WH, Thomas, DP, and Lytle, CD

M

Malik, L: *see* Pussegoda, LN, Malik, L, and Morrison, J

Man, XTC: *see* Wang, Z, Man, XTC, Finch, RD, and Jansen, BH

Manneschmidt, ET: *see* Iskander, SK, Milella, PP, Pini, A, and Manneschmidt, ET

Marci, G: Fatigue crack propagation threshold: what is it and how is it measured?, May, 220

Marur, PR and Tippur, HV: Evaluation of mechanical properties of functionally graded materials, Nov., 539

McBride, SL: *see* Gong, Z, DuQuesnay, DL, and McBride, SL

McLellan, DL and McLellan, MM: Establishing mechanical property allowables for metals, May, 293

McLellan, MM: *see* McLellan, DL and McLellan, MM

Meeker, WQ: *see* Pascual, FG and Meeker, WQ

Milella, PP: *see* Iskander, SK, Milella, PP, Pini, A, and Manneschmidt, ET

Mo, YL and Koan, KJ: Investigation of welding effect on rebars using neural networks, May, 285

Moidu, AK, Sinclair, AN, and Spelt, JK: Determination of fracture energy using the peel test, May, 247

Morrison, J: *see* Pussegoda, LN, Malik, L, and Morrison, J

Morrissett, TW: *see* Lee, Y-L, Wehner, TJ, Lu, M-W, Morrissett, TW, and Pakalnins, E

Mullins, AG: *see* Gunaratne, M, Stinnette, P, Mullins, AG, Kuo, CL, and Echelberger, WF, Jr.

Mussot-Hoinard, G and Ferron, G: Testing device for the mechanical characterization of wood beams or plates under bending compression, Nov., 582

N

Nagaraj, TS: *see* Pandian, NS, Raju, PSN, and Nagaraj, TS

Nelson, BR: *see* Segall, AE, Shelleman, DL, Pan, MJ, Landy, RA, and Nelson, BR

Ni, C: *see* Chui, YH and Ni, C

Nixon, WA: *see* Wei, Y, Nixon, WA, and Shi, Z

Norton, MP: *see* Gong, Y and Norton, MP

O

Obaidat, MT and Al-Smadi, ZA: Additional comments about a modified theodolite instrument: conceptual work, Sept., 510

P

Pakalnins, E: *see* Lee, Y-L, Wehner, TJ, Lu, M-W, Morrissett, TW, and Pakalnins, E

Palma, ES, Lourenco, OR, and Gomes, PTV: Influence of x-radiation on behavior of strain gages, July, 387

Pan, MJ: *see* Segall, AE, Shelleman, DL, Pan, MJ, Landy, RA, and Nelson, BR

Pandey, RK:
see Sriharsha, HK, Anantharaman, S, Chatterjee, S, and Pandey, RK
see Verma, BB, Pandey, RK, and Chinnadurai, R

Pandian, NS
Rajasekhar, C, and Sridharan, A: Studies of the specific gravity of some indian coal ashes, May, 177
Raju, PSN, and Nagaraj, TS: Stress-state permeability relationships for clays with coarse fraction, July, 358

Papadakis, EP: Ultrasonic wave measurements of elastic moduli E, G, and μ for product development and design calculations, May, 240

Pascual, FG and Meeker, WQ: Modified sudden death test: planning life tests with a limited number of test positions, Sept., 434

Patton-Mallory, M
Pellicane, PJ, and Smith, FW:
Experimental analysis of bolted joints in wood, Jan., 45
Modeling bolted connections in wood: a three-dimensional finite-element approach, March, 115
Qualitative assessment of failure in bolted connections: Maximum Stress criterion, Sept., 498
Qualitative assessment of failure in bolted connections: Tsai-Wu criterion, Sept., 489

Pellicane, PJ and Robinson, G:
Effect of construction adhesive and joist variability on the deflection behavior of commercial wood floors, Nov., 609
see Patton-Mallory, M, Pellicane, PJ, and Smith, FW

Pereira, JM: *see* Rabzak, C, Pereira, JM, and Roberts, GD

Picotto, GB: *see* Jensen, CP, Jorgensen, JF, Garnaes, J, Picotto, GB, and Gori, G

Pierdominici, VJB, Jr., Doucette, JM, Coyne, L, Cyr, WH, Thomas, DP, and Lytle, CD: Ability of quality assurance tests to detect punctured latex condoms with potential for virus penetration, Jan., 10

Pini, A: *see* Iskander, SK, Milella, PP, Pini, A, and Manneschmidt, ET

Pussegoda, LN, Malik, L, and Morrison, J: Measurement of crack arrest fracture toughness of a ship steel plate, May, 187

R

Rabzak, C, Pereira, JM, and Roberts, GD: Adhesively bonded strain gages for extended use at 315°C on polymers, July, 367

Rajasekhar, C: *see* Pandian, NS, Rajasekhar, C, and Sridharan, A

Raju, PSN: *see* Pandian, NS, Raju, PSN, and Nagaraj, TS

Read, DT: Piezo-actuated microtensile test apparatus, May, 255

Reed, TD: *see* Rosowsky, DV, Reed, TD, and Tyner, KG

Ritter, JC: *see* Burch, IA, Ritter, JC, Saunders, DS, and Underwood, JH

Roberts, GD: *see* Rabzak, C, Pereira, JM, and Roberts, GD

Robinson, G: *see* Pellicane, PJ and Robinson, G

Robinson, RG and Allam, MM: Role of filter paper separators on the response of clays under long-duration sustained loading, Sept., 463

Rogers, AD, Lee-Sullivan, P, and Bremner, T: Method of fatigue testing of concrete highway joint sealants in shear, May, 234

Romano, D: *see* Bray, A, Barbato, G, Franceschini, F, Levi, R, Romano, D, and Zompi, A

Rosowsky, DV, Reed, TD, and Tyner, KG: Establishing uplift design values for metal connectors in light-frame construction, Sept., 426

S

Saliklis, EP, Cramer, SM, and Hermanson, JC: Measuring the triaxial load-deformation response of orthotropic materials subjected to large and small strain regimes, Sept., 444

Salivar, GC and Goree, JG: Applicability of ASTM standard test specimens to fracture and fatigue crack growth of discontinuous-fiber composites, July, 336

Salman, A, Goulias, D, and Elias, V: Durability of geosynthetics based on accelerated thermo-oxidation testing, Sept., 472

Saunders, DS: *see* Burch, IA, Ritter, JC, Saunders, DS, and Underwood, JH

Schaeffer, SL, Johnson, RL, and Lewis, WB: Impact force comparison of polymers: molded-notch versus cut-notch using the ASTM D 256 izod impact test method, March, 151

Scott, W and Donovan, A: Comparison of surface texture measurement by stylus and fiber optic transducers, Jan., 70

Segal, L: Thermal diagnostic method for vehicle brakes, Sept., 506

Segall, AE, Shelleman, DL, Pan, MJ, Landy, RA, and Nelson, BR: Probabilistic study of the influence of hanger alignment on the reliability of refractory furnace roof anchors, March, 138

Sharpe, WN, Jr.: Potential optical standard for resistance strain gages, Sept., 481

Sheehan, MS: *see* Sickels-Taves, LB and Sheehan, MS

Shelleman, DL: *see* Segall, AE, Shelleman, DL, Pan, MJ, Landy, RA. amd Nelson, BR

Shi, Z: *see* Wei, Y, Nixon, WA, and Shi, Z

Shook, SM: *see* Bradtmueller, JP, Hunt, MO, and Shook, SM

Sickels-Taves, LB and Sheehan, MS: Strategy for mimicking voids in historic masonry, July, 393

Sinclair, AN: *see* Moidu, AK, Sinclair, AN, and Spelt, JK

Singh, SP and Gorzynski, M: Effect of vibration as a cause of leakage in aluminum beer cans in palletized loads, July, 389

Skrzypek, S: *see* Lin, G, Skrzypek, S, Li, D, and Eadie, RL

Smith, FW: *see* Patton-Mallory, M, Pellicane, PJ, and Smith, FW

Smith, FW: *see* Patton-Mallory, M, Pellicane, PJ, and Smith, FW

Spelt, JK: *see* Moidu, AK, Sinclair, AN, and Spelt, JK

Sridharan, A: *see* Pandian, NS, Rajasekhar, C, and Sridharan, A

Sriharsha, HK, Anantharaman, S, Chatterjee, S, and Pandey, RK: Computer program to aid in fatigue precracking of fracture toughness test specimens, Sept., 513

Stinnette, P: *see* Gunaratne, M, Stinnette, P, Mullins, AG, Kuo, CL, and Echelberger, WF, Jr.

Straughan, WT, Tantirungrojchai, N, Guice, LK, and Lin, H: Creep test of cured-in-place pipe material under tension, compression, and bending, Nov., 594

T

Tantirungrojchai, N: *see* Straughan, WT, Tantirungrojchai, N, Guice, LK, and Lin, H

Taylor, ST: *see* Zhu, YT, Butt, DP, Taylor, ST, and Lowe, TC

Tew, BW: *see* Church, JR and Tew, BW

Thomas, DP: *see* Pierdominici, VJB, Jr., Doucette, JM, Coyne, L, Cyr, WH, Thomas, DP, and Lytle, CD

Thomson, PF: *see* Khoddam, S, Lam, YC, and Thomson, PF

Tian, P, Zaman, MM, and Laguros, JG: Variation of resilient modulus of aggregate base and its influence on pavement performance, July, 329

Tippur, HV: *see* Marur, PR and Tippur, HV

To, TM: *see* Lytle, CD, Clavet, CR, Chaput, MP, Varney, GW, To, TM, and Carey, RF

Tobler, RL: *see* Cheng, YW, Filla, BJ, and Tobler, RL

Toropov, AI and Grosso, M: Dynamic calibration of impact test instruments, July, 315

Tyner, KG: *see* Rosowsky, DV, Reed, TD, and Tyner, KG

U

Underwood, JH: *see* Burch, IA, Ritter, JC, Saunders, DS, and Underwood, JH

V

van der Zwaag, S: *see* Braam, JJ and van der Zwaag, S

Varney, GW: *see* Lytle, CD, Clavet, CR. Chaput, MP, Varney, GW, To, TM, and Carey, RF

Verma, BB, Pandey, RK, and Chinnadurai, R: Effect of loading parameters on post-overload fatigue crack closure, Nov., 602

W

Wang, Z, Man, XTC, Finch, RD, and Jansen, BH: Dynamic behavior and vibration monitoring of reinforced concrete beams, Sept., 405

Wehner, TJ: *see* Lee, Y-L, Wehner, TJ, Lu, M-W, Morrissett, TW. amd Pakalnins, E

Wei, Y, Nixon, WA, and Shi, Z: Evaluation of wear resistance of snow plow blade cutting edges using the scratch test method, Nov., 527

Wennhage, P and Zenkert, D: Testing of sandwich panels under uniform pressure, March, 101

Wu, A: Neural-based analog IC parametric fault diagnostic system with discriminant simulation sampling, Nov., 555

Wu, Y-S: *see* Li, M, Xu, B-H, and Wu, Y-S

X

Xu, B-H: *see* Li, M, Xu, B-H, and Wu, Y-S

Y

Yang, L and Fatemi, A: Cumulative fatigue damage mechanisms and quantifying parameters: a literature review, March, 89

Z

Zaman, MM: *see* Tian, P, Zaman, MM, and Laguros, JG

Zenkert, D: *see* Wennhage, P and Zenkert, D

Zhang, S: *see* He, Q, Chen, G, and Zhang, S

Zhu, JH and Anderson, SA: Corrections for triaxial tests on undisturbed soils, May, 277

Zhu, YT, Butt, DP, Taylor, ST, and Lowe, TC: Evaluation of a modified weibull distribution for describing the strength of ceramic fibers and whiskers with varying diameters, March, 144

Zompi, A: *see* Bray, A, Barbato, G, Franceschini, F, Levi, R, Romano, D, and Zompi, A

Journal of Testing and Evaluation
Subject Index
Volume 26, 1998

A

Abrasion
Pin-on-disk corrosion-wear test (Friedersdorf, FJ and Holcomb, GR), July, 352

Acoustic emission
Measurement and interpretation of fatigue crack growth in 7075 aluminum alloy using acoustic emission monitoring (Gong, Z, DuQuesnay, DL, and McBride, SL), Nov., 567
Monitoring crack advance using acoustic emission and combined acoustic emission and potential drop in Zr-2.5%Nb (Lin, G, Skrzypek, S, Li, D, and Eadie, RL), Jan., 15

Adhesives
Effect of construction adhesive and joist variability on the deflection behavior of commercial wood floors (Pellicane, PJ and Robinson, G), Nov., 602

Aggregate
Variation of resilient modulus of aggregate base and its influence on pavement performance (Tian, P, Zaman, MM, and Laguros, JG), July, 329

Asphalt concrete
Adapting superpave technology for design of hot recycled mixes (Foo, KY and Kandhal, PS), May, 203

Asphalt mixes
Adapting superpave technology for design of hot recycled mixes (Foo, KY and Kandhal, PS), May, 203
Asphalt-rubber mixture behavior and design (wet process) (Goulias, DG and Ali, AH), July, 306

B

Bending
Testing device for the mechanical characterization of wood beams or plates under bending compression (Mussot-Hoinard, G and Ferron, G), Nov., 582

Binder
Adapting superpave technology to design of hot recycled mixes (Foo, KY and Kandhal, PS), May, 203

Bolted joints
Bearing strength of white oak pegs in red oak and douglas fir timbers (Church, JR and Tew, BW), March, 109
Experimental analysis of bolted joints in wood (Patton-Mallory, M, Pellicane, PJ, and Smith, FW), Jan., 45
Modeling bolted connections in wood: a three-dimensional finite-element approach (Patton-Mallory, M, Smith, FW, and Pellicane, PJ), March, 115
Qualitative assessment of failure in bolted connections: Tsai-Wu criterion (Patton-Mallory, M, Pellicane, PJ, and Smith, FW), Sept., 489

Buildings
X-ray piping diagnostic system (Kajiwara, G), July, 346

C

Carburized steel Evaluation of the fracture toughness of the deep-carburized layer (Fu, Y, Gu, Y, and Batchelor, AW), May, 198

Clays
Role of filter paper separators on the response of clays under long-duration sustained loading (Robinson, RG and Allam, MM), Sept., 463

Composites
Adhesively bonded strain gages for extended use at 315°C on polymers (Rabzak, C, Pereira, JM, and Roberts, GD), July, 367
Dissipated energy of composite materials—Part I: Cyclic dynamic stress (Bledzki, AK and Gassan, J), Sept., 467

Compression
Creep test of cured-in-place pipe material under tension, compression, and bending (Straughan, WT, Tantirungrojchai, N, Guice, LK, and Lin, H), Nov., 594
Experimental analysis of bolted joints in wood (Patton-Mallory, M, Pellicane, PJ, and Smith, FW), Jan., 45
Testing device for the mechanical characterization of wood beams or plates under bending compression (Mussot-Hoinard, G and Ferron, G), Nov., 582

Computerized systems
Computer program to aid in fatigue precracking of fracture toughness test specimens (Sriharsha, HK, Anantharaman, S, Chatterjee, S, and Pandey, RK), Sept., 513
Design and performance of an automated test facility for hot-compression testing (Cheng, YW, Filla, BJ, and Tobler, RL), Jan., 38

Construction
Investigation of welding effect on rebars using neural networks (Mo, YL and Koan, KJ), May, 285
Probabilistic study of the influence of hanger alignment on the reliability of refractory furnace roof anchors (Segall, AE, Shelleman, DL, Pan, MJ, Landy, RA, and Nelson, BR), March, 138

Corrosion
Pin-on-disk corosion-wear test (Friedersdorf, FJ and Holcomb, GR), July, 352

Crack-arrest toughness
Crack-arrest testing of irradiated nuclear reactor pressure vessel steels at the Oak Ridge National Laboratory (Iskander, SK, Milella, PP, Pini, A, and Manneschmidt, ET), Nov., 546

Crack growth
Crack arrest fracture toughness testing of naval construction steels (Burch, IA, Ritter, JC, Saunders, DS, and Underwood, JH), May, 269
Fatigue crack propagation threshold: what is it and how is it measured? (Marci, G), May, 220
Influence of corrosion on the fatigue properties of Al 7075-T6 (Du, ML, Chiang, FP, Kagwade, SV, and Clayton, CR), May, 260
International survey of small-crack research (Hamm, RW and Johnson, WS), March, 168
Monitoring crack advance using acoustic emission and combined acoustic emission and potential drop in Zr-2.5%Nb (Lin, G, Skrzypek, S, Li, D, and Eadie, RL), Jan., 15

Crack length
International survey of small-crack research (Hamm, RW and Johnson, WS), March, 168

© 1998 by the American Society for Testing and Materials

Crack-length monitoring
International survey of small-crack research (Hamm, RW and Johnson, WS), March, 168

Crack propagation Fatigue crack propagation threshold: what is it and how is it measured? (Marci, G), May, 220

Crack threshold
Fatigue crack propagation threshold: what is it and how is it measured? (Marci, G), May, 220

Creep
Measurement of fatigue-creep dynamic back stress and strain rate equation of a Fe-Ni-Cr alloy (He, Q, Chen, G, and Zhang, S), Nov., 617

Cup method
Alternative procedure for the analysis of data from the cup method measurements for determination of water vapor transmission properties (Kumaran, MK), Nov., 575

D

Damage mechanics
Cumulative fatigue damage mechanisms and quantifying parameters: a literature review (Yang, L and Fatemi, A), March, 89

Damping
Shape of mechanical hysteresis loops for metals under harmonic loading (Bovsunovsky, AP and Kratko, AG), Jan., 31

Data acquisition
Automatic procedure for evaluation of Young's Modulus of metallic materials (Bray, A, Barbato, G, Franceschini, F, Levi, R, Romano, D, and Zompi, A), Jan., 64

Diagnostic system
Neural-based analog IC parametric fault diagnostic system with discriminant simulation sampling (Wu, A), Nov., 555

Distribution
Materials fatigue life distribution: a maximum entropy approach (Gong, Y and Norton, MP), Jan., 53

Drop height
Dynamic calibration of impact test instruments (Toropov, AI and Grosso, M), July, 315

Durability
Durability of geosynthetics based on accelerated thermo-oxidation testing (Salman, A, Goulias, D, and Elias, V), Sept., 472
Evaluation of wear resistance of snow plow blade cutting edges using the scratch test method (Wei, Y, Nixon, WA, and Shi, Z), Nov., 527

Dynamic fractures
Note on one-point-bend impact fracture experiments with curved specimens (Giovanola, JH, Klopp, RW, and Kirkpatrick, SW), Jan., 79

E

Elastic modulus
Ultrasonic wave measurements of elastic moduli E, G, and μ for product development and design calculations (Papadakis, EP), May, 240

Elastic strain
Evaluation of mechanical properties of functionally graded materials (Marur, PR and Tippur, HV), Nov., 539
Experimental justification for proposed changes to the measurement of K_{Ic} using ASTM E 399 (Joyce, JA), Sept., 455

Electrical conductor
Eddy current decay and resistivity measurements on longitudinally grooved high-purity aluminum bars (Gillenwater, MW, Hartwig, KT, and Hua, CY), July, 320

Electronics
Comparison of surface texture measurement by stylus and fiber optic transducers (Scott, W and Donovan, A), Jan., 70

Endoscope sheath
Evaluation of three methodologies for testing disposable ENT endoscope sheaths as viral barriers (Lytle, CD, Clavet, CR, Chaput, MP, Varney, GW, To, TM, and Carey, RF), Nov., 587

Entropy
Materials fatigue life distribution: a maximum entropy approach (Gong, Y and Norton, MP), Jan., 53

Experiments
Modified sudden death test: planning life tests with a limited number of test positions (Pascual, FG and Meeker, WQ), Sept., 434

F

Fasteners
Bearing strength of white oak pegs in red oak and douglas fir timbers (Church, JR and Tew, BW), March, 109

Fatigue
Applicability of ASTM standard test specimens to fracture and fatigue crack growth of discontinuous-fiber composites (Salivar, GC and Goree, JG), July, 336
Computer program to aid in fatigue precracking of fracture toughness test specimens (Sriharsha, HK, Anantharaman, S, Chatterjee, S, and Pandey, RK), Sept., 513
Influence of corrosion on the fatigue properties of Al 7075-T6 (Du, ML, Chiang, FP, Kagwade, SV, and Clayton, CR), May, 260
Method of fatigue testing of concrete highway joint sealants in shear (Rogers, AD, Lee-Sullivan, P, and Bremner, T), May, 234

Fatigue data
Cumulative fatigue damage mechanisms and quantifying parameters: a literature review (Yang, L and Fatemi, A), March, 89

Fatigue life distribution
Materials fatigue life distribution: a maximum entropy approach (Gong, Y and Norton, MP), Jan., 53

Fatigue limit
Statistical evaluation of the staircase and the ArcSin $\sqrt{P}$ methods for determining the fatigue limit (Braam, JJ and van der Zwaag, S), March, 125

Fatigue testing
Effect of loading parameters on post-overload fatigue crack closure (Verma, BB, Pandey, RK, and Chinnadurai, R), Nov., 602
H_2-optimal control of random loading for a laboratory fatigue test (Li, M, Xu, B-H, and Wu, Y-S), Nov., 619

Fibers
Evaluation of a modified Weibull distribution for describing the strength of ceramic fibers and whiskers with varying diameters (Zhu, YT, Butt, DP, Taylor, ST, and Lowe, TC), March, 144

Filaments
Evaluation of a modified Weibull distribution for describing the strength of ceramic fibers and whiskers with varying diameters (Zhu, YT, Butt, DP, Taylor, ST, and Lowe, TC), March, 144

Finite element method
Method of finding the effective length of the specimen used in the hot torsion test and recommendations on geometry of the test specimen (Khoddam, S, Lam, YC, and Thomson, PF), March, 157
Modeling bolted connections in wood: a three-dimensional finite-element approach (Patton-Mallory, M, Smith, FW, and Pellicane, PJ), March, 115
Qualitative assessment of failure in bolted connections: maximum stress criterion (Patton-Mallory, M, Pellicane, PJ, and Smith, FW), Sept., 498

Fly ash
Studies of the specific gravity of some Indian coal ashes (Pandian, NS, Rajasekhar, C, and Sridharan, A), May, 177

Force
Piezo-actuated microtensile test apparatus (Read, DT), May, 255

Fracture
Applicability of ASTM standard test specimens to fracture and fatigue crack growth of discontinuous-fiber composites (Salivar, GC and Goree, JG), July, 336
Procedure for fracture toughness testing using a chevron-notched crack-arrest specimen (Bonenberger, RJ, Dally, JW, and Fourney, WL), July, 376

Fracture energy
Determination of fracture energy using the peel test (Moidu, AK, Sinclair, AN, and Spelt, JK), May, 247

Fracture testing
Measurement and interpretation of fatigue crack growth in 7075 aluminum alloy using acoustic emission monitoring (Gong, Z, DuQuesnay, DL, and McBride, SL), Nov., 567

Fracture toughness
Crack arrest fracture toughness testing of naval construction steels (Burch, IA, Ritter, JC, Saunders, DS, and Underwood, JH), May, 269
Evaluation of the fracture toughness of the deep-carburized layer (Fu, Y, Gu, Y, and Batchelor, AW), May, 198
Experimental justification for proposed changes to the measurement of K_{Ic} using ASTM E 399 (Joyce, JA), Sept., 455
Measurement of crack arrest fracture toughness of a ship steel plate (Pussegoda, LN, Malik, L, and Morrison, J), May, 187
Procedure for fracture toughness testing using a chevron-notched crack-arrest specimen (Bonenberger, RJ, Dally, JW, and Fourney, WL), July, 376
Results from a round robin on a standard method for measurement of fracture toughness (Landes, JD and Brown, K), July, 396

Friction
New approach to measuring transverse properties of structural tubing by a ring test—experimental investigation (Arsene, S and Bai, J), Jan., 26

Furnaces
Probabilistic study of the influence of hanger alignment on the reliability of refractory furnace roof anchors (Segall, AE, Shelleman, DL, Pan, MJ, Landy, RA, and Nelson, BR), March, 138

G

Gas turbines
Design and development of a high-speed bearing test apparatus (Kim, K), July, 301

Geometric surface area
Method of finding the effective length of the specimen used in the hot torsion test and recommendations on geometry of the test specimen (Khoddam, S, Lam, YC, and Thomson, PF), March, 157

H

Historic preservation
Strategy for mimicking voids in historic masonry (Sickels-Taves, LB and Sheehan, MS), July, 393

Hysteresis
Shape of mechanical hysteresis loops for metals under harmonic loading (Bovsunovsky, AP and Kratko, AG), Jan., 31

I

Impact wear
Evaluation of mechanical properties of functionally graded materials (Marur, PR and Tippur, HV), Nov., 539
Impact force comparison of polymers: molded-notch versus cut-notch using the ASTM D 256 izod impact test method (Schaeffer, SL, Johnson, RL, and Lewis, WB), March, 151
Note on one-point-bend impact fracture experiments with curved specimens (Giovanola, JH, Klopp, RW, and Kirkpatrick, SW), Jan., 79

Insulation
Interlaboratory comparison of the ASTM standard test methods for water vapor transmission of materials (E 96–95) (Kumaran, MK), March, 83

Interferometry
Potential optical standard for resistance strain gages (Sharpe, WN, Jr.), Sept., 481

Irradiation
Influence of x-radiation on behavior of strain gages (Palma, ES, Lourenco, OR, and Gomes, PTV), July, 387

J

Joints
Method of fatigue testing of concrete highway joint sealants in shear (Rogers, AD, Lee-Sullivan, P, and Bremner, T), May, 234
Stress-strain relationship of common wire nails under reversed cyclic loading (Chui, YH and Ni, C), Sept., 420

Joists
Effect of construction adhesive and joist variability on the deflection behavior of commercial wood floors (Pellicane, PJ and Robinson, G), Nov., 609

L

Latex condom
Ability of quality assurance tests to detect punctured latex condoms with potential for virus penetration (Pierdominici, VJB, Jr., Doucette, JM, Coyne, L, Cyr, WH, Thomas, DP, and Lytle, CD), Jan., 10

Leaks
Effect of vibration as a cause of leakage in aluminum beer cans in palletized loads (Singh, SP and Gorzynski, M), July, 389

Liquid porosity
Stress-state permeability relationships for clays with coarse fraction (Pandian, NS, Raju, PSRN, and Nagaraj, TS), July, 358

Loading
H_2-optimal control of random loading for a laboratory fatigue test (Li, M, Xu, B-H, and Wu, Y-S), Nov., 619
Role of filter paper separators on the response of clays under long-duration sustained loading (Robinson, RG and Allam, MM), Sept., 463

Loading rates
Testing of sandwich panels under uniform pressure (Wennhage, P and Zenkert, D), March, 101

M

Mechanical properties
Establishing mechanical property allowables for metals (McLellan, DL and McLellan, MM), May, 293
New approach to measuring transverse properties of structural tubing by a ring test—experimental investigation (Arsene, S and Bai, J), Jan., 26

Membrane compliance
Corrections for triaxial tests on undisturbed soils (Zhu, JH and Anderson, SA), May, 277

Membrane resistance
Corrections for triaxial tests on undisturbed soils (Zhu, JH and Anderson, SA), May, 277

Metallography
Automatic procedure for evaluation of Young's Modulus of metallic materials (Bray, A, Barbato, G, Franceschini, F, Levi, R, Romano, D, and Zompi, A), Jan., 64

Metals
Cumulative fatigue damage mechanisms and quantifying parameters: a literature review (Yang, L and Fatemi, A), March, 89
Establishing uplift design values for metal connectors in light-frame construction (Rosowsky, DV, Reed, TD, and Tyner, KG), Sept., 426

Metrology
Vickers hardness indentations measured with atomic force microscopy (Jensen, CP, Jorgensen, JF, Garnaes, J, Picotto, GB, and Gori, G), Nov., 532

Microhardness
Evaluation of the fracture toughness of the deep-carburized layer (Fu, Y, Gu, Y, and Batchelor, AW), May, 198

Microspecimens
Piezo-actuated microtensile test apparatus (Read, DT), May, 255

Models
Investigation of welding effect on rebars using neural networks (Mo, YL and Koan, KJ), May, 285

Monitoring
Monitoring crack advance using acoustic emission and combined acoustic emission and potential drop in Zr-2.5%Nb (Lin, G, Skrzypek, S, Li, D, and Eadie, RL), Jan., 15

N

Nails
Stress-strain relationship of common wire nails under reversed cyclic loading (Chui, YH and Ni, C), Sept., 420

Neural network
Neural-based analog IC parametric fault diagnostic system with discriminant simulation sampling (Wu, A), Nov., 555

Nondestructive testing (NDT)
Dynamic behavior and vibration monitoring of reinforced concrete beams (Wang, Z, Man, XTC, Finch, RD, and Jansen, BH), Sept., 405

Nuclear technology
Crack-arrest testing of irradiated nuclear reactor pressure vessel steels at the Oak Ridge National Laboratory (Iskander, SK, Milella, PP, Pini, A, and Manneschmidt, ET), Nov., 546

O

Organics
Compressibility relations for peat and organic soil (Gunaratne, M, Stinnette, P, Mullins, AG, Kuo, CL, and Echelberger, WF, Jr.), Jan., 1

Orthotropic materials
Measuring the triaxial load-deformation response of orthotropic materials subjected to large and small strain regimes (Saliklis, EP, Cramer, SM, and Hermanson, JC), Sept., 444

P

Parameters
Thermal diagnostic method for vehicle brakes (Segal, L), Sept., 506

Pavements
Method of fatigue testing of concrete highway joint sealants in shear (Rogers, AD, Lee-Sullivan, P, and Bremner, T), May, 234

Peat
Compressibility relations for peat and organic soil (Gunaratne, M, Stinnette, P, Mullins, AG, Kuo, CL, and Echelberger, WF, Jr.), Jan., 1

Peel test
Determination of fracture energy using the peel test (Moidu, AK, Sinclair, AN, and Spelt, JK), May, 247

Pendulum tester
Dynamic calibration of impact test instruments (Toropov, AI and Grosso, M), July, 315
Impact force comparison of polymers: molded-notch versus cut-notch using the ASTM D 256 izod impact test method (Schaeffer, SL, Johnson, RL, and Lewis, WB), March, 151

Permeability
Stress-state permeability relationships for clays with coarse fraction (Pandian, NS, Raju, PSRN, and Nagaraj, TS), July, 358

Piezoelectric
Piezo-actuated microtensile test apparatus (Read, DT), May, 255

Piping
Creep test of cured-in-place pipe material under tension, compression, and bending (Straughan, WT, Tantirungrojchai, N, Guice, LK, and Lin, H), Nov., 594
X-ray piping diagnostic system (Kajiwara, G), July, 346

Plastic dissipation
Determination of fracture energy using the peel test (Moidu, AK, Sinclair, AN, and Spelt, JK), May, 247

R

Refractories
Probabilistic study of the influence of hanger alignment on the reliability of refractory furnace roof anchors (Segall, AE, Shelleman, DL, Pan, MJ, Landy, RA, and Nelson, BR), March, 138

Reproducibility
Interlaboratory comparison of the ASTM standard test methods for water vapor transmission of materials (E 96–95) (Kumaran, MK), March, 83

Resilient modulus
Variation of resilient modulus of aggregate base and its influence on pavement performance (Tian, P, Zaman, MM, and Laguros, JG), July, 329

Ring test
New approach to measuring transverse properties of structural tubing by a ring test—experimental investigation (Arsene, S and Bai, J), Jan., 26

S

Sandwich specimens
Testing of sandwich panels under uniform pressure (Wennhage, P and Zenkert, D), March, 101

Scratch test
Evaluation of wear resistance of snow plow blade cutting edges using the scratch test method (Wei, Y, Nixon, WA, and Shi, Z), Nov., 527

Settlement
Compressibility relations for peat and organic soil (Gunaratne, M, Stinnette, P, Mullins, AG, Kuo, CL, and Echelberger, WF, Jr.), Jan., 1

Shear modulus
Mechanical properties of laminated veneer lumber via five-point bending test (Bradtmueller, JP, Hunt, MO, and Shook, SM), March, 132

Shear strength
Mechanical properties of laminated veneer lumber via five-point bending test (Bradtmueller, JP, Hunt, MO, and Shook, SM), March, 132
Ultimate strength of resistance spot welds subjected to combined tension and shear (Lee, Y-L, Wehner, TJ, Lu, M-W, Morrissett, TW, and Pakalnins, E), May, 213

Shear testing
Mechanical properties of laminated veneer lumber via five-point bending test (Bradtmueller, JP, Hunt, MO, and Shook, SM), March, 132
Qualitative assessment of failure in bolted connections: Tsai-Wu criterion (Patton-Mallory, M, Pellicane, PJ, and Smith, FW), Sept., 489
Testing of sandwich panels under uniform pressure (Wennhage, P and Zenkert, D), March, 101

Specific gravity
Studies of the specific gravity of some indian coal ashes (Pandian, NS, Rajasekhar, C, and Sridharan, A), May, 177

Specimen condition
Note on one-point-bend impact fracture experiments with curved specimens (Giovanola, JH, Klopp, RW, and Kirkpatrick, SW), Jan., 79

Stability
Asphalt-rubber mixture behavior and design (wet process) (Goulias, DG and Ali, AH), July, 306

Standards
Potential optical standard for resistance strain gages (Sharpe, WN, Jr.), Sept., 481

Statistical modeling
Establishing mechanical property allowables for metals (McLellan, DL and McLellan, MM), May, 293

Statistics
Statistical evaluation of the staircase and the ArcSin $\sqrt{P}$ methods for determining the fatigue limit (Braam, JJ and van der Zwaag, S), March, 125

Steel plate
Measurement of crack arrest fracture toughness of a ship steel plate (Pussegoda, LN, Malik, L, and Morrison, J), May, 187

Steels
Design and performance of an automated test facility for hot-compression testing (Cheng, YW, Filla, BJ, and Tobler, RL), Jan., 38
Ultrasonic wave measurements of elastic moduli E, G, and μ for product development and design calculations (Papadakis, EP), May, 240

Strain gages
Adhesively bonded strain gages for extended use at 315°C on polymers (Rabzak, C, Pereira, JM, and Roberts, GD), July, 367
Influence of x-radiation on behavior of strain gages (Palma, ES, Lourenco, OR, and Gomes, PTV), July, 387

Strain rates
Measurement of fatigue-creep dynamic back stress and strain rate equation of a Fe-Ni-Cr alloy (He, Q, Chen, G, and Zhang, S), Nov., 617

Strength
Establishing mechanical property allowables for metals (McLellan, DL and McLellan, MM), May, 293
Evaluation of a modified Weibull distribution for describing the strength of ceramic fibers and whiskers with varying diameters (Zhu, YT, Butt, DP, Taylor, ST, and Lowe, TC), March, 144
Ultimate strength of resistance spot welds subjected to combined tension and shear (Lee, Y-L, Wehner, TJ, Lu, M-W, Morrissett, TW, and Pakalnins, E), May, 213

Stress
Qualitative assessment of failure in bolted connections: maximum stress criterion (Patton-Mallory, M, Pellicane, PJ, and Smith, FW), Sept., 498

Stress analysis
Crack arrest fracture toughness testing of naval construction steels (Burch, IA, Ritter, JC, Saunders, DS, and Underwood, JH), May, 269
Dissipated energy of composite materials—Part I: Cyclic dynamic stress (Bledzki, AK and Gassan, J), Sept., 467
Effect of loading parameters on post-overload fatigue crack closure (Verma, BB, Pandey, RK, and Chinnadurai, R), Nov., 602
Modeling bolted connections in wood: a three-dimensional finite-element approach (Patton-Mallory, M, Smith, FW, and Pellicane, PJ), March, 115
Shape of mechanical hysteresis loops for metals under harmonic loading (Bovsunovsky, AP and Kratko, AG), Jan., 31
Statistical evaluation of the staircase and the ArcSin $\sqrt{P}$ methods for determining the fatigue limit (Braam, JJ and van der Zwaag, S), March, 125

Stress measurement
Bearing strength of white oak pegs in red oak and douglas fir timbers (Church, JR and Tew, BW), March, 109

Structural tests
Thermal diagnostic method for vehicle brakes (Segal, L), Sept., 506

Sudden death test
Modified sudden death test: planning life tests with a limited number of test positions (Pascual, FG and Meeker, WQ), Sept., 434

Superconductivity
Eddy current decay and resistivity measurements on longitudinally grooved high-purity aluminum bars (Gillenwater, MW, Hartwig, KT, and Hua, CY), July, 320

Surface analysis
Comparison of surface texture measurement by stylus and fiber optic transducers (Scott, W and Donovan, A), Jan., 70

Surface roughness
Influence of corrosion on the fatigue properties of Al 7075-T6 (Du, ML, Chiang, FP, Kagwade, SV, and Clayton, CR), May, 260

T

Temperature
Design and performance of an automated test facility for hot-compression testing (Cheng, YW, Filla, BJ, and Tobler, RL), Jan., 38

Tension testing
Experimental analysis of bolted joints in wood (Patton-Mallory, M, Pellicane, PJ, and Smith, FW), Jan., 45
Ultimate strength of resistance spot welds subjected to combined tension and shear (Lee, Y-L, Wehner, TJ, Lu, M-W, Morrissett, TW, and Pakalnins, E), May, 213

Test procedures
Ability of quality assurance tests to detect punctured latex condoms with potential for virus penetration (Pierdominici, VJB, Jr., Doucette, JM, Coyne, L, Cyr, WH, Thomas, DP, and Lytle, CD), Jan., 10
Impact force comparison of polymers: molded-notch versus cut-notch using the ASTM D 256 izod impact test method (Schaeffer, SL, Johnson, RL, and Lewis, WB), March, 151
Measurement of crack arrest fracture toughness of a ship steel plate (Pussegoda, LN, Malik, L, and Morrison, J), May, 187
Results from a round robin on a standard method for measurement of fracture toughness (Landes, JD and Brown, K), July, 396
Studies of the specific gravity of some indian coal ashes (Pandian, NS, Rajasekhar, C, and Sridharan, A), May, 177

Theodolite
Additional comments about a modified theodolite instrument: conceptual work (Obaidat, MT and Al-Smadi, ZA), Sept., 510

Thermo-oxidation
Durability of geosynthetics based on accelerated thermo-oxidation testing (Salman, A, Goulias, D, and Elias, V), Sept., 472

Torsion
Method of finding the effective length of the specimen used in the hot torsion test and recommendations on geometry of the test specimen (Khoddam, S, Lam, YC, and Thomson, PF), March, 157

Transducer
Comparison of surface texture measurement by stylus and fiber optic transducers (Scott, W and Donovan, A), Jan., 70

Triangulation
Additional comments about a modified theodolite instrument: conceptual work (Obaidat, MT and Al-Smadi, ZA), Sept., 510

Triaxial tests
Corrections for triaxial tests on undisturbed soils (Zhu, JH and Anderson, SA), May 277

Turbine components
Design and development of a high-speed bearing test apparatus (Kim, K), July, 301

V

Vibration
Dynamic behavior and vibration monitoring of reinforced concrete beams (Wang, Z, Man, XTC, Finch, RD, and Jansen, BH), Sept., 405
Effect of Vibration as a cause of leakage in aluminum beer cans in palletized loads (Singh, SP and Gorzynski, M), July, 389

Vickers hardness
Vickers hardness indentations measured with atomic force microscopy (Jensen, CP, Jorgensen, JF, Garnaes, J, Picotto, GB, and Gori, G), Nov., 532

Viruses
Ability of quality assurance tests to detect punctured latex condoms with potential for virus penetration (Pierdominici, VJB, Jr., Doucette, JM, Coyne, L, Cyr, WH, Thomas, DP, and Lytle, CD), Jan., 10
Evaluation of three methodologies for testing disposable ENT endoscope sheaths as viral barriers (Lytle, CD, Clavet, CR, Chaput, MP, Varney, GW, To, TM, and Carey, RF), Nov., 587

Voids
Strategy for mimicking voids in historic masonry (Sickels-Taves, LB and Sheehan, MS), July, 393

W

Water vapor
Alternative procedure for the analysis of data from the cup method measurements for determination of water vapor transmission properties (Kumaran, MK), Nov., 575
Interlaboratory comparison of the ASTM standard test methods for water vapor transmission of materials (E 96–95) (Kumaran, MK), March, 83

Weldments
Investigation of welding effect on rebars using neural networks (Mo, YL and Koan, KJ), May, 285

Wood
Establishing uplift design values for metal connectors in light-frame construction (Rosowsky, DV, Reed, TD, and Tyner, KG), Sept., 426
Measuring the triaxial load-deformation response of orthotropic materials subjected to large and small strain regimes (Saliklis, EP, Cramer, SM, and Hermanson, JC), Sept., 444

Y

Young's modulus
Automatic procedure for evaluation of Young's Modulus of metallic materials (Bray, A, Barbato, G, Franceschini, F, Levi, R, Romano, D, and Zompi, A), Jan., 64
Ultrasonic wave measurements of elastic moduli E, G, and μ for product development and design calculations (Papadakis, EP), May, 240